and volume of its work. However, the applicant must have enough properly qualified employees to keep up with the volume of work in process, and may not reduce the number of its employees below that necessary to efficiently produce airworthy work.

- (c) Each repair station shall determine the abilities of its supervisors and shall provide enough of them for all phases of its activities. However, the Administrator may determine the ability of any supervisor by inspecting his employment and experience records or by a personal test. Each supervisor must have direct supervision over working groups but need not have overall supervision at management level. Whenever apprentices or students are used in working groups on assemblies or other operations that might be critical to the aircraft, the repair station shall provide at least one supervisor for each 10 apprentices or students, unless the apprentices or students are integrated into groups of experienced workers.
- (d) Each person who is directly in charge of the maintenance functions of a repair station must be appropriately certificated as a mechanic or repairman under part 65 of this chapter and must have had at least 18 months of practical experience in the procedures, practices, inspection methods, materials, tools, machine tools, and equipment generally used in the work for which the station is rated. Experience as an apprentice or student mechanic may not be counted in computing the 18 months of experience. In addition, at least one of the persons so in charge of maintenance functions for a station with an airframe rating must have had experience in the methods and procedures prescribed by the Administrator for returning aircraft to service after 100-hour, annual, and progressive inspections.
- (e) Each limited repair station shall have employees with detailed knowledge of the particular maintenance function or technique for which it is rated, based on attending a factory school or long experience with the product or technique involved.

## §145.41 Recommendation of persons for certification as repairmen.

- (a) When a person applies for a domestic repair station certificate and rating(s) or additional rating(s) that require a repairman, that person must—
- (1) Recommend at least one person for certification as a repairman;
- (2) Certify to the Administrator that the person recommended meets the requirements of §65.101 of this chapter; and
- (3) Certify that the person recommended is able to perform and supervise the assigned work.
- (b) Each person recommended per paragraph (a)(1) of this section must be at or above the level of shop foreman or department head or be responsible for supervising the work performed by the repair station. A qualified person so recommended may be certificated as a repairman.

(Secs. 313, 314, and 601 through 610, of the Federal Aviation Act of 1958, as amended (49 U.S.C. 1354, 1355, 1421 through 1430); sec. 6(c), Dept. of Transportation Act (49 U.S.C. 1655(c)))

[Doc. No. 21269, 47 FR 33390, Aug. 2, 1982]

## §145.43 Records of supervisory and inspection personnel.

- (a) Each applicant for a domestic repair station certificate and rating, or for an additional rating, must have, and each certificated domestic repair station shall maintain, a roster of—
- (1) Its supervisory personnel, including the names of the officials of the station that are responsible for its management and the names of its technical supervisors, such as foreman and crew chiefs; and
- (2) Its inspection personnel, including the names of the chief inspector and those inspectors who make final airworthiness determinations before releasing an article to service.
- (b) The station shall also provide a summary of the employment of each person whose name is on the roster. The summary must contain enough information as to each person on the roster to show compliance with the experience requirements of this subpart, including—
- (1) His present title (e.g., chief inspector, metal shop foreman, etc.);

## § 145.45

(2) His total years of experience in the type of work he is doing;

(3) His past employment record, with names of places and term of employ-

ment by month, and year;

(4) The scope of his present employment (e.g., airframe overhaul, airframe final assembly, engine inspection, department, etc.); and

- (5) The type and number of the mechanic or repairman certificate that he holds, and the ratings on that certificate.
- (c) The station shall change the roster, as necessary, to reflect—
- (1) Terminating the employment of any person whose name is on the roster:
- (2) Assigning any person to duties that require his name to be carried on the roster; or
- (3) Any appreciable change in the duties and scope of assignment of any person whose name is on the roster.
- (d) The station shall keep the roster and employment summaries required by this section, subject to inspection by the Administrator upon his request.
- (e) A domestic repair station may not use the services of a person directly in charge of maintenance or alteration unless it keeps current records on him as required by this section.

[Doc. No. 1157, 27 FR 6662, June 13, 1962, as amended by Amdt. 145–5, 31 FR 8585, June 21, 1966; Amdt. 145–15, 41 FR 47230, Oct. 28, 1976]

## §145.45 Inspection systems.

(a) An applicant for a repair station certificate, and rating or for an additional rating, must have an inspection system that will produce satisfactory quality control and conform to paragraphs (b) to (f) of this section.

(b) The applicant's inspection personnel must be thoroughly familiar with all inspection methods, techniques, and equipment used in their specialty to determine the quality or airworthiness of an article being maintained or altered. In addition, they must—

(1) Maintain proficiency in using various inspection aids intended for that purpose:

(2) Have available and understand current specifications involving inspection tolerances, limitations, and procedures established by the manufacturer of the product being inspected and with other forms of inspection information such as FAA airworthiness di- rectives and bulletins; and

- (3) In cases where magnetic, fluorescent, or other forms of mechanical inspection devices are to be used, be skilled in operating that equipment and be able to properly interpret defects indicated by it.
- (c) The applicant must provide a satisfactory method of inspecting incoming material to insure that, before it is placed in stock for use in an aircraft or part thereof, it is in a good state of preservation and is free from apparent defects or malfunctions.
- (d) The applicant must provide a system of preliminary inspection of all articles he maintains to determine the state of preservation or defects. He shall enter the results of each inspection on an appropriate form supplied by it and keep the form with the article until it is released to service.
- (e) The applicant must provide a system so that before working on any airframe, powerplant, or part thereof that has been involved in an accident, it will be inspected thoroughly for hidden damage, including the areas next to the obviously damaged parts. He shall enter the results of this inspection on the inspection form required by paragraph (d) of this section.
- (f) At the time he applies for a repair station certificate, the applicant must provide a manual containing inspection procedures, and thereafter maintain it in current condition at all times. The manual must explain the internal inspection system of the repair station in a manner easily understood by any employee of the station. It must state in detail the inspection requirements in paragraphs (a) to (e) of this section, and the repair station's inspection system including the continuity of inspection responsibility, samples of inspection forms, and the method of executing them. The manual must refer whenever necessary to the manufacturer's inspection standards for the maintenance of the particular article. The repair station must give a copy of the manual to each of its supervisory and inspection personnel and make it available to its other personnel. The repair station is responsible